



Hi-Gain[™] Wireless 300N Router with Range Amplifier

MODEL: HAWNR3



PACKAGE CONTENTS:

- Hi-Gain™ Wireless 300N Router with Range Amplifier
- Two 3dBi Hi-Gain Omni Directional Antennas
- One Mac/PC CD
- One RJ-45 Ethernet Cable
- One Power Adapter
- Easy to follow Quick Installation Guide

Go online and instantly share your internet access between computers in your home or office! The performance of most standard routers (strength & data) decrease significantly past a coverage radius of 200 feet. The HAWNR3 Wireless 300N Router has a built-in range amplifier and uses Hi-Gain Technology to expand this coverage radius and boost WiFi performance. With up to 6X the transfer speed and up to 300% the distance of a standard Wireless-G network, the HAWNR3 Router makes downloading multimedia files or data more enjoyable.

Along with wireless connectivity, the HAWNR3 has 4 wired 10/100Mbps Ethernet ports for connecting your computers that do not have wireless access. It also offers the latest in wireless security, ensuring that your files and network are safe from outside intruders. Installation of the HAWNR3 is simple and straight forward. Just open your web browser and log into the secure setup page to setup the router in minutes.

For additional wireless range coverage, the HAWNR3 features two removable antennas for quick and easy antenna upgrade. The HAWNR3 Router is compatible with all Hawking Hi-Gain Wireless Antennas – select one that fits your wireless needs.

FEATURES

- Instantly share a broadband Internet connection with up to 253 users
- High power output, of up to 500mW compared to a standard 50mW
- Ultra-Fast Data Transfer speeds and Superior Wireless Range using Hi-Gain™ Technology
- Supports 2.4GHz Wireless 801.11 b/g/n network capability allowing for data transfer speeds of up to 300Mbps!
- 64/128-bit WEP, WPA, and WPA2 wireless data encryption.
- MAC address filtering (Only allow specific wireless device of your choice to connect to this access point).
- Four wired LAN ports and one wired WAN port (10/100M)
- Auto MDI / MDI-X function for all wired Ethernet ports.
- Support DHCP (Server/Client) for easy IP-address setup.
- Allows you to monitor the access point's status: DHCP Client Log, System Log, Security Log and Device/Connection

SYSTEM REQUIREMENTS

- Computer or network device(s) with wired or wireless network interface card.
- Web browser (Microsoft Internet Explorer 4.0 or above, Netscape Navigator 4.7 or above, Opera web browser, Mozilla Firefox web browser or Safari web browser).
- An available AC power socket (100 240 V, 50/60Hz)



SPECIFICATIONS:

Standard: IEEE 802.11 b/g/n Frequency Band: 2.4000-2.4835 GHz Security: WEP 64/128, WPA, WPA2, IEEE802.1

Hardware CPU + Wireless Chipsets: Realtek RTL8196C+RTL8192CE Flash: 2MB SDRAM: 16MB WAN Ports: 10/100M UTP Port x 1 LAN Ports: 10/100M UTP Port x 4 Antenna: 2x 3dBi Dipole antennas Power: 12VDC, 1A Switching Power Adapter Output Power spec: 11n (40MHz)@MCS15: 23+/-1.5dBm 11n (20MHz)@MCS15: 23+/-1.5dBm 11g@54Mbps: 23+/-1.5dBm 11b@11Mbps: 26+/-1.5dBm Receive Sensitivity spec: 11n (40MHz)@MCS15: -69+/-2dBm 11n (20MHz)@MCS15: -73+/-2dBm 11g@54Mbps: -78+/-2dBm 11b@11Mbps: -89+/-2dBm

Weight: 0.42 lbs (Body only) Dimension: 6 x 4.1 x 1.1 inches Temperature: 32~104°F (0 ~ 40°C) Humidity: 10-90% (NonCondensing) Certification: FCC, CE

HAWKING TECHNOLOGIES, INC.


35 HAMMOND SUITE 150 · IRVINE, CA 92618

Sales Phone: 888.662.8828 Email: sales@hawkingtech.com Technical Support Phone: 888.202.3344 Email: techsupport@hawkingtech.com



PERFORMANCE GUIDE

The performance of most standard routers (strength & data transfer) decrease significantly past a coverage radius of 200 feet. The HAWNR3 Router has a built-in range amplifier and Hi-Gain Technology to expand its coverage radius and boost WiFi performance. As a result, the HAWNR3 reduces wireless deadspots and allows WiFi enabled devices to roam freely.



Hawking HAWNR3 Wireless Network Wireless Connection Wired Connection Tr



MODEL: HAWNR3